

Description

ISS model # EGY-C334-LV 3x3 AR-AFFF (Alcohol Resistant Aqueous Film-Forming Foam) Low Viscosity Concentrate combines

fluoro- and hydrocarbon-surfactant technologies to provide superior fire and vapor suppression for Class B, polar solvent and hydrocarbon fuel fires. The low viscosity of this concentrate enables ease of proportioning in a wide range of equipment such as in-line eductors, balanced pressure systems, built-in systems aboard ARFF (Aircraft Rescue and Fire Fighting) and other emergency response vehicles. This synthetic foam concentrate is intended for forceful or gentle firefighting applications at 3% solution on hydrocarbon fuels and at 3% solution on polar solvent fuels in fresh, salt, or hard water.

ISS model # EGY-C334-LV foam solution utilizes three suppression mechanisms intended for rapid fire knockdown and superior

Burn back resistance:

- The foam blanket blocks oxygen supply to the fuel
- Liquid drains from the foam blanket and forms either:
 - An aqueous film on a hydrocarbon fire, or
 - A polymeric membrane on a polar solvent fire which suppresses the vapor and seals the fuel surface.
- The water content of the foam solution produces a cooling effect for additional fire suppression.

TYPICAL PHYSIOCHEMICAL PROPERTIES

Appearance	Viscous yellow liquid
Density	1.03 + 0.02 g/ml
pH	7.0 - 8.5
Refractive Index	1.3600 minimum
Viscosity*	1000 + 300 cPs at 77 °F (25 °C)
Viscosity*	1100 + 300 cPs at 35 °F (2 °C)
Spreading Coefficient	3 dynes/cm minimum at 3% dilution
Pour Point	10 °F (-12 °C)
Freeze Point	7 °F (-14 °C)

Brookfield Viscometer Spindle #4, speed 60 rpm

ISS model # EGY-C334-LV Concentrate is a non-Newtonian fluid that is both pseudo plastic and thixotropic. Due to these properties, dynamic viscosity will decrease as shear increases.

Application

ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate is intended for use on both types of Class B fires: hydrocarbon fuels with low water solubility, such as crude oils, gasolines, diesel fuels, and aviation fuels; and polar solvent fuels with appreciable water solubility, such as methyl and ethyl alcohol, acetone, and methyl ethyl ketone.

The concentrate also has excellent wetting properties that can effectively combat Class A fires. It may also be used in conjunction with dry chemical agents to provide even greater fire suppression performance.

Approvals, Listings, and Standards

ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate is designed in accordance with National Fire Protection Association (NFPA) Standard 11 for Low-, Medium-, and High-Expansion Foam. The concentrate is approved, listed, qualified under, or meets the requirements of the following specifications and standards:

- UL Standard 162, Foam Liquid Concentrates
 - UL Listed for use with an extensive array of proportioning and discharge equipment, including sprinklers as required by NFPA 16

This concentrate is only FM Approved in conjunction with the specific proportioning equipment and discharge devices as shown in the Approval Guide (www.ApprovalGuide.com)



Foaming Properties

ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate may be effectively applied using most conventional foam discharge equipment at the correct dilution with fresh, salt, or hard water. For optimum performance, water hardness should not exceed 500 ppm expressed as calcium and magnesium.

ISS model # EGY-C334-LV Concentrate requires low energy to foam and the foam solution may be applied with aspirating and non-aspirating discharge devices. Aspirating discharge devices typically produce expansion ratios from 3.5:1 to 10:1, depending on the type of device and the flow rate. Non-aspirating devices, such as handline water fog/stream nozzles or standard sprinkler heads, typically produce expansion ratios from 2:1 to 4:1. Medium-expansion discharge devices typically produce expansion ratios from 20:1 to 60:1.

Material of Construction Compatibility

o help avoid corrosion, galvanized pipe and fittings should never be used in contact with undiluted ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate. Refer to Technical Bulletin "Acceptable Materials of Construction" for recommendations and guidance regarding compatibility of foam concentrates with common materials of construction in the firefighting foam industry.

The environmentally-mindful ISS model # EGY-C334-LV Concentrate formulation contains short-chain, C-6 fluorochemicals manufactured using a telomer-based process. The telomer process produces no PFOS, and these C-6 materials do not breakdown to yield PFOA. The fluorochemicals used in the concentrate meet the goals of the U.S. Environmental Protection Agency 2010/15 PFOA Stewardship Program.



TYPICAL FOAM CHARACTERISTICS ** (Fresh and Salt Water)

	Hydrocarbon
Proportioning Rate	3%
Expansion Ratio	> 7
25% Drain Time (min:sec)	> 8:00
50% Drain Time (min:sec)	> 15:00

** per EN 1568-3, 2008 protocol

Proportioning

The recommended operational temperature range for ISS model # EGY-C334-LV 3X3 AR-AFFF Concentrate is 35 °F to 120 °F (2 °C to 49 °C). This foam concentrate can be correctly proportioned using most conventional, properly calibrated, in-line proportioning equipment such as:

- Balanced and in-line balanced pressure pump proportioners
- Balanced pressure bladder tanks and ratio flow controllers
- Around-the-pump type proportioners
- Fixed or portable in-line venturi type proportioners
- Handline nozzles with fixed eductor /pick-up tubes

For immediate use: The concentrate may also be premixed with fresh or salt water to 3% solution for hydrocarbon fuel fires or a 3% solution for polar solvent fuel fires.

For delayed use: Consult Technical Services for guidance regarding suitability of a pre-mix solution (fresh water only).

Storage and Handling

ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate should be stored in the original supplied package (HDPE totes, drums, or pails) or in the recommended foam system equipment as outlined in Technical Bulletin "Storage of Foam Concentrates". A thin layer up to 1/4 in.

(6 mm) thick of appropriate-grade mineral oil may be applied to the surface of the foam concentrate stored in a fixed, atmospheric storage container to help minimize evaporation. Consult for further guidance regarding the use of mineral oil to help seal the surface of AR-AFFF concentrates.

The concentrate should be maintained within the recommended operational temperature range. Freezing of the product

Should be avoided. If, however, the product freezes during transport or storage, it must be thawed and inspected for signs of separation. If separation has occurred or is suspected, ISS model # EGY-C334-LV Concentrate should be mechanically mixed until homogeneous, and additional testing may be required after mixing to verify product quality. Factors affecting the foam concentrate's long-term effectiveness include temperature exposure and cycling, storage container characteristics, air exposure, evaporation, dilution, and contamination. The effective life of ISS model # EGY-C334-LV Concentrate can be maximized through optimal storage conditions and proper handling. ISS foam concentrates have demonstrated effective firefighting performance with contents stored in the original package under proper conditions for more than 10 years.

Mixing ISS model # EGY-C334-LV Concentrate with other foam concentrates for long-term storage is not recommended. Use in conjunction with comparable 3x3 AR-AFFF products for immediate incident response is appropriate.

Inspection

ISS model # EGY-C334-LV 3X3 AR-AFFF Concentrate should be inspected periodically in accordance with NFPA 11, EN 13565-2, or other relevant standard. A representative concentrate sample should be sent to Foam Analytical

Services or other qualified laboratory for quality analysis per the applicable standard. An annual inspection and sample analysis is typically sufficient, unless the product has been exposed to unusual conditions.

Ordering Information

ISS model # EGY-C334-LV 3x3 AR-AFFF Concentrate is available in pails, drums, totes, or bulk shipment.

Totes are not UL/ULC approved packaging.

Part No.	Description	Shipping Weight
Drums		
EGY-C334-LV	55 gal (208 L)	495 lb (224.5 kg)
Totes		
EGY-C334-LV	265 gal (1003 L)	2463 lb (1117 kg)

E-mail: info@isssystems.com